



## **EDIsecure**® DCP 340+ Direct Card Printer


### A HIGH-PERFORMANCE, DOUBLE-SIDED PRINTER FOR YOUR GROWING NEEDS

- Double-side printed cards in brilliant color with crisp, sharp graphics
- High-speed printing of up to 190 full-color and up to 1,000 monochrome cards per hour
- Convenient, automatic front card loading and output
- User-friendly design for easy operation and maintenance
- Advanced cleaning roller system
- Various ribbon combinations available
- Ideal for medium to high volume applications for corporations, organizations, hospitals, health facilities, and universities, for photo IDs and loyalty cards

The double-sided, edge-to-edge *EDIsecure*® DCP 340+ Direct Card Printer is the ideal solution for card personalization of medium to higher volume applications. High quality printing results in attractive cards with a professional look. With its high class design, low noise level and small footprint, it fits perfectly on every desk. Photo IDs and loyalty cards can be created now quickly by the perfect combination of speed and highest quality.

The DCP 340+ has an extremely impressive print speed of up to 190 full-color cards per hour. The print speed jumps even up to 1,000 cards per hour when printing monochrome cards. Easy handling is guaranteed by the quick-change of supplies through re-loadable cartridges, operator replaceable printheads, front-facing card feeding and output, and continuous card cleaning. The advanced cleaning roller system removes particles that could scratch cards, damage printheads or diminish print quality. The smart printer driver shows all information on the PC screen, including message prompts, color image previews and online help.

Choose with barcodes and magnetic stripe encoding the machine-readable technology that fits with your access control and other automated systems.



### FEATURES:

- Large ribbon capacity as well as large input and output hoppers to ensure continuous printing
- Front-facing, automatic card feeding and output
- Optimized print ribbons
- Quick ribbon change, cartridge loads in a snap
- Operator replaceable printheads
- Advanced cleaning roller system to avoid scratches on cards
- Automatic ribbon detection and low ribbon warning
- Audible and visual message prompts
- Ribbon saver features for monochrome ribbons

### SUPPLIES:

- 5 Panel Color Ribbon (YMCKO): 500 cards/ribbon
- 7 Panel Color Ribbon (YMCKOKO): 300 cards/ribbon
- Monochrome Black Ribbon (K): 1500 cards/ribbon
- Monochrome White Ribbon (W): 1500 cards/ribbon
- Monochrome Silver Ribbon (S): 1500 cards/ribbon

(Other ribbons on request)

### OPTIONS:

- Magnetic stripe encoding (HiCo and LoCo)

### CONFIGURE YOUR CARD IDENTITY SYSTEM, ASK FOR:

- EDIsecure® Card Management Software Suite
- EDIsecure® Image Capture Modules
- EDIsecure® Image Enhancement Software
- EDIsecure® Card Materials

### SPECIFICATIONS OF DCP 340+

|                            |  |
|----------------------------|--|
| Print Method               | Color dye sublimation and monochrome thermal transfer  |
| Print Mode                 | Double-sided edge-to-edge direct card printing   |
| Print Speed                | Full color: up to 190 cards per hour (single-sided)<br>Monochrome: up to 1,000 cards per hour (single-sided) |
| Print Resolution           | 300 dpi  |
| Printhead                  | Operator replaceable, 24 month warranty, no count limitation using EDIsecure® Cards                          |
| Card Types                 | All PVC and Composite PVC Cards of ISO ID-1/CR-80 size, 85.60 x 53.98 mm                                     |
| Card Thickness             | 0.25 – 1.3 mm  |
| Input Hopper Capacity      | 100 cards (0.76 mm)  |
| Output Hopper Capacity     | 40 cards (0.76 mm)   |
| Interface                  | USB 1.1  |
| Operating System Support   | MS Windows® 2000, XP, and VISTA*   |
| Printer Dimensions (WxDxH) | 198 x 546 x 241 mm   |
| Weight                     | approx. 5 kg   |
| Power Supply               | 100/120 V and 220/240 V, 50/60Hz<br>FCC, CE, UL, GOST, and CCC approved                                      |
| Operating Environment      | 15°C to 35°C, 20% to 80% non-condensing humidity   |

\* in preparation

Digital Identification Solutions AG  
Germany  
Phone: + 49 711 341 689 - 0  
Email: mail@digital-identification.com

Digital Identification Solutions Pte. Ltd.  
Singapore 757718  
Phone: + 65 6352 8364  
Email: mail@sg.digital-identification.com

Digital Identification Solutions (Branch)  
Dubai, United Arab Emirates  
Phone: + 971 4 2045 316  
Email: mail@uae.digital-identification.com

Digital Identification Solutions (Beijing) Co. Ltd.  
P.R. China  
Phone: + 86 10 6437 4376  
Email: mail@cn.digital-identification.com

Digital Identification Solutions S. de R.L. de C.V.  
México  
Phone: + 52 442 2171 768 - 0  
Email: mail@mx.digital-identification.com

Digital Identification Solutions LLC  
United States of America  
Phone: + 1 864 272 1199  
Email: mail@us.digital-identification.com

vps ID Systems GmbH  
Germany  
Phone: + 49 7243 5488 - 0  
Email: info@vps.de